

# UPS5000-E Series

## (50-800kVA)

### Introduction

---

UPS5000-E Series (50-800kVA) is an advanced modular UPS based on Huawei's extensive experience in digital technology and power electronics. Benefiting from high performance DSP and high speed communication technology, the UPS5000-E system achieves leading expandability and availability. Its high efficiency, high availability match the requirements of cloud data center perfectly.

### Scenarios

---

- Data centers in headquarter or disaster recovery data centers
- Internet data centers
- Large cloud computing data centers

### Features

---

#### Reliable

- 138-485Vac ultra-wide input voltage range, suitable for the worst power grid
- Redundant design for modules, elimination of the single point of failure
- iPower pre-warnings for key components in case of power supply interruption

#### Efficient

- High efficiency up to 95%-96% at most frequently-used load rate
- Intelligent hibernation technology ensures efficient UPS operation
- Single UPS capacity up to 800kVA, 50% footprint saving, more IT rack space

#### Simple

- Hot swappable power module, bypass module and control module, simple maintenance and expansion in 5 minutes
- iPower real time monitoring system for UPS, PDU and batteries, elimination of manual routing inspection



UPS5000-E-200/300K



UPS5000-E-400/500K

# Specifications

Model		UPS5000-E-200K	UPS5000-E-300K	UPS5000-E-400K	UPS5000-E-500K	UPS5000-E-600K	UPS5000-E-800K
Rated Capacity (kVA/kW)		50-200	50-300	50-400	50-500	50-600	50-800
Number of Power Modules		1-4	1-6	1-8	1-10	1-12	1-16
Mains Input	Input Wiring	3Ph+PE (Neutral wire: optional*)					
	Rated Voltage	380/400/415Vac					
	Voltage Range	138-485Vac (305-485Vac for 100% load; 138-305Vac for 40%-100% load)					
	Frequency Range	40-70Hz					
	Total Harmonic Distortion	THDi<3% for 100% linear load					
	Input Power Factor	0.99					
Bypass Input	Rated Voltage	380/400/415Vac					
	Input Frequency	50/60±6Hz					
Battery	Rated Voltage	360-528Vdc (The number of batteries can be selected from 30 to 44; 40 batteries in default)					
Output	Output Wiring	3Ph+N+PE					
	Voltage	380/400/415Vac±1%					
	Frequency	Tracking the bypass input (Normal mode); 50/60Hz±0.05% (Battery mode)					
	Waveform	Sine wave (THDv<1% for linear load)					
	Overload Capacity	Inverter: 110% overload for 60 minutes; 125% overload for 10 minutes; 150% overload for 1 minute					
System	Output Power Factor	1					
	Efficiency	Up to 96%					
	Expandability	8					
Environment	Operating Temperature	0-40°C					
	Storage Temperature	-40 to 70°C					
	Relative Humidity	0%-95% (No condensing)					
	Operating Altitude	0-1000m. Above 1000m, derating rate based on EN/IEC 62040-3					
	Audible Noise	66-75dB					
Others	Height × Width × Depth (mm)	2000 × 600 × 850		2000 × 1200 × 850		2000 × 1400 × 850	2000 × 2400 × 850
	Weight (kg)	285~390	275~450	465~710	515~830	705~1090	1075~1540
	Certifications	EN/IEC 62040-1; EN/IEC 62040-2; EN/IEC 62040-3; CE; CB; RoHS, REACH, WEEE, etc.					
	Communications	Dry contacts, RS485, SNMP					

\* Without neutral wire, it's TN-C system.

Notice:

1. The UPS series are for commercial/industrial use and not used for life support equipment;
2. The critical systems concerning economic and public security must adopt power supply architecture that comply with Uptime TIER III or TIER IV requirements stated in TIA942.

Copyright © Huawei Technologies Co., Ltd. 2018. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

## General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

## HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base  
Bantian Longgang  
Shenzhen 518129, P.R. China  
Tel: +86-755-28780808

[www.huawei.com](http://www.huawei.com)